

Commercial Carpet Tiles:

26000 Nobel [Review Patterns](#)

26070 Matrix



www.royacanadainc.com



MATRIX

**MATRIX & MOTION
FOR ALL DEMANDING APPLICATIONS**

The first step is building better commercial carpet in using a superior fiber. At Roya Manufacturing & Supply Canada, Inc., we use one of the most specified brands of commercial carpet fiber, Invista DSDN 6.6.

Better Performance
For carpet to be a true value, it must look as good years into the future as it does the day it was installed. It must withstand all the abuse that an active workplace can produce. With proper carpet maintenance, no other fiber meets these challenges.

Exceptional Color Fastness
We add color to the fiber during the extension process. Because the color is integral part of the fiber, it will not wear or fade. The color in our fiber also holds up exceptionally well to UV light, atmospheric contaminants, and harsh cleaning agents, so it will last and look better and longer.

Exceptional Value
One important aspect of Invista DSDN 6.6 fiber is unchanging: it meets ROYA's rigorous standards for quality and performance. Its long life, unsurpassed performance and environmental friendliness make carpet manufactured on Invista DSDN 6.6 fiber an exceptional value.

ROYA

[Review Patterns](#)

26080 Motion



[Review Patterns](#)

26030 Prism **[Review Patterns](#)**

26002 Social Architecture












26050 Infinito (Indent)

26015 Universe Plus (Indent)

TECHNICAL

[Click here for 'Installation of Roya Contract Modular Carpet'](#)

TECHNICAL SPECIFICATIONS - MATRIX & MOTION

	STYLE NAME	MATRIX & MOTION
	CONSTRUCTION	High / Low Loop
	FACE YARN	Invisia DSDN 6.6
	PILE YARN WEIGHT	700 g/m ²
	PILE HEIGHT	5.5 - 3.0 mm
	GAUGE	1/12 G
	TOTAL THICKNESS	8 mm ± 0.50 mm (0.24 inches)
	TOTAL WEIGHT	5400 g/m ² ± 100 g/m ²
	BACKING	Primary backing of polyester spun bonded with a Secondary backing of vinyl reinforced with fibre glass
	TILE SIZE	50 cm x 50 cm (19.7" x 19.7")
	DIMENSION STABILITY	DIN - 54318 < 0.15%
	ELECTROSTATIC PROPENSITY	Static Electricity AATCC - 134 < 3.5 KV (20% RH, 70° F)
	FLAMMABILITY	Passes ASTM E 648 Class I
	APPLICATION	Suitable for any type of heavy contract
	SAMPLES	Instant sample delivery upon request
	INSTALLATION METHOD	Monolithic & Quarter - Turn
	WARRANTY	Useful Life

In keeping with ROYA MANUFACTURING & SUPPLY CANADA INC.'s corporate environmental commitment, this sample brochure is produced with recycled and recyclable materials.



Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.

ROYA MANUFACTURING & SUPPLY CANADA Inc.

ROYA

www.royacanadainc.com

International Sales - Fax: (514) 410-3822 - 800-387-2272 E-mail: roya@royacanadainc.com

© Royca Manufacturing & Supply Canada Inc., Toronto