

# TECHNICAL DATA SHEET

sheet EVM-001

## METAL MOSAIC & TILES

### The Metal Mosaic & Tiles

The tesserae are produced from a 1mm non-marine stainless steel Double Brushed surface finish for the natural color sheets and Single Brushed surface finish and PVD plated (Physical Vapor Deposition) surface finish for the colored sheets with an additional protective clear coating.

The metal is bonded with a polyurethane adhesive onto a white porcelain supporting tile (Australian Innovative Patent no.2002101029)  
 Sheets have excellent abrasion, corrosion and oxidation resistance.  
 Everstone Metal Mosaic can be simply cut with any continuous-segmented Diamond Blade or Diamond Wire wet-saw tile cutter (re.: GEMINI Saw) and installed using white adhesive.  
 Use of Score and Break is not suited.

For specific installation grout or adhesive, we recommend you to contact your local favorite adhesive manufacturer.

### APPLICATIONS:

- Internal surfaces – Yes
- External surfaces/Wet areas – Subject to use

### PRODUCT DATA:

- Tesserae total thickness- 5mm~9mm (refer to catalogue)
- Cotton-Polyethylene rear mesh
- White Latex and Polyurethane Adhesive
- Available in 5 standard Everstone colors
- Sizes available from 20x20mm mosaic up to 400x400mm tile or to customer specification\*
- Available in Brushed and Antique surface finish
- Also available for open corner Wall installations, in 3, 2 and 1Edges (corner) format
- Refer to catalogue for standard full range of products
- Refer to '*Modular Size Chart*' for actual Tesserae sizes



### BLENDS MIXED COLOUR COMPOSITION: (Metal Plus)

SMG001: S/S + Vortex S/S + Nickel + Glass ES58 (25% EACH)	SMG002: S/S + Nickel + Copper + Glass ES49 (25% EACH)
---	---

\* conditions apply