

Commercial Vinyl Centra

Specifications:



Domestic
heavy




Commercial
very heavy



Industrial
heavy



Slip
resistant




Dimensional
stability



Thermal
resistance



Chemical
resistant



Light
fastness

Level of use EN ISO 10874 -	23 – 34 - 43
Total thickness -	2.00 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	HyperGuard+
Total weight -	2378 g/m ²
Width -	2 m & 3 m
Standard length -	25 m
Inflammability EN 13501 -	Bfl-S1
Slip resistance EN 13893 -	DS
Slip restraint EN 16165 Annex B -	R10
Residual indentation EN ISO 24343-1 -	0.07 mm
Furniture leg resistance -	Pass
Electrical resistance EN 1081 -	10 ⁹ Ohm
Dimensional stability EN ISO 23999 -	0.04 %
Heat insulation -	0.0139 (m ² .K/W)
Light fastness -	≥6
Underfloor heating -	Suitable (max 27°C)
Resistance to chemicals -	Very good
Warranty	7 years Commercial 15 years Residential

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, Christchurch 8042, New Zealand
robertmalcolm.co.nz


robert malcolm

