

# Residential Vinyl Step

## Specifications:



Domestic  
medium



Natural  
feel



Slip  
resistant




Reduces  
noise




Thermal  
resistance



Protectonite  
PU



Long  
lasting



Stocked in  
New Zealand

European classification EN ISO 10874 -	22
Total thickness -	2.00 mm
Wear layer -	0.20 mm
Wear layer treatment -	Natural Feel
Total weight -	1450 g/m <sup>2</sup>
Width -	2 m
Standard length -	30 m
Slip restraint EN 16165 Annex B -	R10
Inflammability EN 13501 -	Cfl-S1
Acoustical insulation EN ISO 717-2 -	16 dB
Underfloor heating -	Suitable
Thermal conductivity ISO 8302 (1991) -	0.073 – 0.119 W / mK
Thermal resistance EN 12667:2001-01-	0.007 - 06066 m <sup>2</sup> K/W
Resistance to household chemicals -	Very good
Warranty (year) -	5 years Residential Use

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
10 Establishment Drive, Christchurch 8042, New Zealand  
robertmalcolm.co.nz



robert malcolm

