L.V.T.

Moduleo Intoo Square Tile

Specifications:















Dimensional stability

Slip resistant

Castor whee resistant

Thermal resistance

Long lasting

Stain resistant

Light fastnes

Level of use ISO 10874 -	23 – 33
Total thickness -	4.5 mm
Wear layer -	0.55 mm
Wear layer PUR treatment -	Protectonite®
Total weight -	7600 g/m ²
Planks -	49.3 x 49.3 cm
Box planks -	8 pc/box, 1.944 m ² /box
Inflammability EN 13501-1 -	Bfl-S1
Critical Radiant Flux EN ISO 9239-1 -	9.8 kW/m2
Scratch resistance -	Class T
Squareness & straightness -	≤ 0.35 mm
Edge detail -	Bevelled edge 4 sides
Slip resistance -	DS
Slip restraint EN 16165 annex B -	R10
Residual indentation EN ISO 24343-1 -	Norm: ≤ 0.10 mm, Average result measured ≤ 0.05 mm
Furniture leg resistance -	No cracks, no damage
Dimensional stability -	Norm: ≤ 0.25 %, Average result measured ≤ 0.05 %
Thermal resistance R -	0.0100 m ² K/W
Electrostatic performance -	< 2 kV
Sound Transmission Class ASTM E90 -	61 dB
Impact Insulation Class ASTM E492 -	65 dB
Castor chair resistance -	No damage to wearlayer, no delamination
Formaldehyde group EN 717-1 -	E1
Light fastness -	≥6
Underfloor heating -	Suitable, max 27°C
Wear Warranty (year) -	25 Residential / 10 Commercial

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products
 such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a
 manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz 10 Establishment Drive, Christchurch 8042, New Zealand robertmalcolm.co.nz

