


L.V.T.

Oslo Plank

Specifications:



Dimensional stability




Slip resistant



Long lasting




Thermal resistance



Great for families



Hypoallergenic



Stocked in New Zealand

Level of Use ISO 10874 -	23 – 31
Total thickness -	2.00 mm
Wear layer -	0.30 mm
Wear layer PUR treatment -	Hexamoll DINCH
Total weight g/M ² -	3031.3 g/m ²
Planks -	121.9 x 18.3 cm
Box planks -	3.34 m ² /box
Inflammability EN 13501-1 -	Bfl-S1
Critical Radiant Flux AS ISO 9239.1-2003 -	10.6 kW/m ²
Squareness & straightness -	Side length mean value – 457.3mm Squareness mean value – 0.038mm Straightness mean value – 0.043mm
Edge detail -	Bevelled edge 4 sides
Slip resistance -	R9
Residual indentation ISO 24343-1-	≤ 0.1 mm
Scratch resistance EN ISO 14565 -	Passed
Furniture leg resistance -	Applied mass 32kg, no visible damage
Dimensional stability -	≤ 0.25 %,
Castor chair resistance -	No visible damage
Emission performance EN16516 -	A+
Underfloor heating -	Suitable, max 27°C
Wear Warranty -	12 years residential

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm