Carpet Tile

Bavaria

Specifications:













resistant



Solution dved nylon

Antistatic

Long lasting

Dimensional stability

Fade resistant

Construction -Multi-Level Loop 100% Universal SDN66 Fibre -1/12" Gauge -Stitches -11 per inch Pile weight -19 oz/yď Average pile height -4 mm ± 0.5 mm Backing -**PVC** with fiberglass Tile size -50 cm x 50 cm Class II, Heavy Commercial Traffic classification -Antimicrobial -Ultra-Fresh Installation method -Quarter Turn; Monolithic Fire test -Class I Pass Anti-static -≤3.5 kV Pass Wear tests r = 2.8Pass Warranties -10 Year Wear Resistance Limited Warranty 10 Year Delamination Limited Warranty 10 Year Dimensional Stability Limited Warranty 10 Year Castor Chairs Limited Warranty

 All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.

10 Year Stain Limited Warranty Life-time Static Limited Warranty

- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz 59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand robertmalcolm.co.nz

