## **Residential Vinyl**

## **Fashion**

## **Specifications:**

















Domestic

Commercial

Slip resistant

Reduces

Light fastness

Thermal resistance

Chemical resistant

European classification -	23 – 32
Total thickness -	2.40 mm
Wear layer -	0.35 mm
Wear layer treatment -	MAT Effect
Total weight -	$1730  \text{g/m}^2$
Width -	2 m
Standard Length	25 m
Slip resistance -	R10
Inflammability -	Cfl-S1
Acoustical insulation -	16 dB
Light fastness -	≥6
Underfloor heating -	Suitable
Thermal resistance -	0.06 m <sup>2</sup> /kW
Resistance to household chemicals -	OK
Warranty (year) -	15 years (Residential use)

• RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

**p** 03 366 9839 **e** office@robertmalcolm.co.nz 59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand **robertmalcolm.co.nz** 

