

Carpet Tile

I Fresh


Specifications:




Castor wheel resistant




Antistatic covering



Long lasting



Dimensional stability



Fade resistant



Construction -	Multi-level loop
Fibre -	Invista Antron Legacy+Glimmer
Gauge -	1/12"
Stitches -	10 per inch
Pile weight -	22 oz/yd ²
Average pile height -	4 mm ± 0.5 mm
Backing -	Eco Ace Backing
Tile size -	50 cm x 50 cm
Traffic classification -	Class II, Heavy Commercial
Antimicrobial -	Ultra-Fresh
Installation method -	Quarter Turn
Fire test -	Class I Pass
Critical Radiant Flux -	5.3 kW/m ²
Anti-static -	≤3.5 kV Pass
Wear tests -	r =2.8 Pass
Warranties -	15 Year Wear Resistance Limited Warranty 15 Year Delamination Limited Warranty 15 Year Dimensional Stability Limited Warranty 15 Year Castor Chairs Limited Warranty 15 Year Stain Limited Warranty Life-time Static Limited Warranty

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz

