


L.V.T.

Moduleo Select

Specifications:



Dimensional stability



Castor wheel resistant




Thermal resistance




Antistatic covering




Stain resistant



Long lasting



Great for families



Stocked in New Zealand

Level of use -	23 – 32
Total thickness -	2.35 mm
Wear layer -	0.40 mm
Wear layer PUR treatment -	Protectonite®
Total weight -	3.821 g/m ²
Planks -	19.6 x 132.0 cm (7.72" x 51.97")
Box planks -	15 pc/box, 3.9 m ² /box (41.98 ft ² /box)
Tiles -	32.9 x 65.9 cm (12.95" x 25.94")
Box tiles -	18 pc/box, 3.9m ² /box (41.98 ft ² /box)
Inflammability -	Bfl-S1
Scratch resistance -	Class T
Squareness & straightness -	≤ 0.35 mm
Slip resistance -	DS
Slip restraint -	R10
Residual indentation -	Norm: ≤ 0.10 mm, Average result measured ≤ 0.03 mm
Furniture leg resistance -	No cracks, no damage
Electrical resistance -	≤ 10 ⁹ Ohm
Dimensional stability -	Norm: ≤ 0.25 %, Average result measured ≤ 0.05 %
Heat insulation -	0.25 w/(m.K)
Thermal resistance R -	0.0100 m ² K/W
Electrostatic performance -	< 2 kV
Acoustic insulation -	4 dB
Castor chair resistance -	No damage to wearlayer, no delamination
Stain resistance -	Very good
Light fastness -	≥ 6
Underfloor heating -	Suitable, max 27°C
Warranty (year) -	15 Residential / 7 Commercial

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

