Residential Vinyl Renaissance

Specifications:

Domestic heavy Commercial moderate	Slip resistant	Reduces	Light fastness	Thermal resistance	Chemical resistant	10
European classification -			1			
Total thickness -	2.60 m	ım				
Wear layer - C			im			
Wear layer treatment -			ffect			
Total weight -		1690 g	/m²			
Width -		2 m &	3 m			
Standard length -		30 m				
Slip resistance -		R10				
Inflammability -		Cfl-S1				
Acoustical insulation -		19 dB				
Light fastness -		≥ 6				
Underfloor heating -			Suitable			
Thermal resistance -			0.04 m ² /kW			
Resistance to household chemicals -			ОК			
Warranty (year) -			rs (Residential	use)		

• RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839
e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



