


Carpet Tile

Roya - Nobel


Specifications:




Solution dyed



Antistatic covering



Long lasting



10 year guarantee

| | |
|-----------------------|---|
| Construction - | High / Medium / Low Loop |
| Fibre - | 100% Solution Dyed Polypropylene |
| Gauge - | 1/8" & 1/4" |
| Stitches - | 31.5/10 cm |
| Pile weight - | 630 g/m ² |
| Total weight - | 5.1 kg/m ² , ± 100 g/m ² |
| Average pile height - | 0.157" avg (4.0 mm) |
| Backing - | Primary - Non woven synthetic fibre Secondary – PVC reinforced with fibreglass |
| Tile size - | 50 cm x 50 cm |
| Installation method - | Quarter Turn |
| Fire test - | Passes BS 4790, 1987. Fully adhere Hot Metal Nut test |
| Anti-static - | 3.0 kV when tested under the standard shuffle test 21°C minus 20% R.H. |
| Warranty (year) - | 10 years |

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

