


Carpet Tile

Sumi Leaf


Specifications:




Solution dyed nylon



Antistatic covering




Dimensional stability



Fade resistant



Stain resistant



Long lasting



Fibre -	100% Nylon (Antron Lumena)
Gauge -	1/10"
Stitches -	10/inch
Total weight -	4.7 kg/m ²
Average pile height -	4 mm to 2.5 mm (± 0.5 mm)
Backing -	Special PVC
Tile size -	50 cm x 50 cm
Installation method -	Quarter Turn
Fire test -	J.F.R.A registered test No. EO 040251
Anti-static -	JIS L 1023, 23°C, 23% RH, Synthetic Leather Sole, 1kV or less
Wear tests -	JIS L 1023-9 (1000 times), 0.1g or less
Warranties -	10 Year Limited Wear 10 Year Limited Edge Ravel 10 Year Limited Zippering 10 Year Limited Delamination

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz

robert malcolm

