

Commercial Vinyl Techno Safe

Specifications:



Domestic heavy



Commercial general




Industrial moderate




Slip resistant




Thermal resistance



Dimensional stability



Light fastness



Stocked in New Zealand

Level of use -	23 – 32 – 41
Total thickness -	2.00 mm
Wear layer -	0.40 mm
Wear layer PUR treatment -	PU Laquer
Total weight -	1850 g/m ²
Width -	2 m
Standard length -	22 m
Inflammability -	Bfl-S1
Slip resistance -	DS
Slip restraint -	R10
Residual indentation -	≤ 0.20 mm
Dimensional stability -	≤ 0.40 %
Light fastness -	≥ 6 – 7
Underfloor heating -	Suitable
Warranty (year) -	8 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

