

Carpet Tile

Allegra

Specifications:




Solution dyed nylon




Antistatic covering



Long lasting




Dimensional stability



Fade resistant



Castor wheel resistant



10 year guarantee

Construction -	Multi-Level Loop	
Fibre -	100% Solution Dyed Nylon	
Gauge -	1/12"	
Stitches -	10 per inch	
Pile weight -	18 oz/yd ²	
Average pile height -	4 mm ± 0.5 mm	
Backing -	PVC with fiberglass	
Tile size -	50 cm x 50 cm	
Traffic classification -	Commercial-Heavy Duty	
Antimicrobial -	Health Guard	
Installation method -	Quarter Turn; Monolithic; Brick; Ashlar	
Fire test -	Class I	Pass
Critical Radiant Flux -	9.5 kW/m ²	
Anti-static -	≤3.5 kV	Pass
Wear tests -	r =2.8	Pass
Warranties -	10 Year Wear Resistance Limited Warranty 10 Year Delamination Limited Warranty 10 Year Dimensional Stability Limited Warranty 10 Year Castor Chairs Limited Warranty 10 Year Stain Limited Warranty Life-time Static Limited Warranty	

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz


robert malcolm