

Commercial Carpet

Aspiring


Specifications:




Solution dyed nylon




Stain resistant




Antistatic covering



Fade resistant



Light fastness



Long lasting



15 year guarantee

Pile fibre -	100% Resistain® Solution Dyed Nylon
Colouration -	Solution Dyed
Machine gauge -	1/10 th Gauge – 39.4/100 mm
Construction -	Level Loop Graphic
Width -	3.66 m (12')
Stitch rate -	34 / 100 mm
Tufted pile weight -	22 oz/yd ² 746 g/m ² (± 5%)
Tufted pile height -	5 mm (± 5%)
Primary backing -	Woven Synthetic
Secondary backing -	Easybac®
9A Fire rating -	Yes (Building is fitted with sprinkler system complying with specification E1.5)
9B Fire rating	Yes
Static generation (AS2834) -	> 3.5 kV
Light fastness -	6 – 7
Resistance to change on wet cleaning -	4 – 5
Pattern repeat -	10 mm x 10 mm
Grading -	Residential Extra Heavy Duty + Stairs Commercial Extra Heavy Duty + Stairs
Warranties -	15 Year Limited Anti-Static 15 Year Limited Colourfast 15 Year Limited Manufacturing / Wear 15 Year Limited Soil Resistant 15 Year Limited Stain Resistant

- Due to dye lot variations, actual material may vary from sample.
- Chair mats are mandatory.
- This carpet must be laid in accordance with AS/NZ Installation Standards.
- All joins must be seam sealed.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

