

# Carpet Tile

# Bavaria

## Specifications:




Solution  
dyed nylon




Antistatic  
covering



Long  
lasting




Dimensional  
stability



Fade  
resistant



Castor wheel  
resistant



10  
year guarantee

Construction -	Multi-Level Loop	
Fibre -	100% Universal SDN66	
Gauge -	1/12"	
Stitches -	11 per inch	
Pile weight -	19 oz/yd <sup>2</sup>	
Average pile height -	4 mm ± 0.5 mm	
Backing -	PVC with fiberglass	
Tile size -	50 cm x 50 cm	
Traffic classification -	Class II, Heavy Commercial	
Antimicrobial -	Ultra-Fresh	
Installation method -	Quarter Turn; Monolithic	
Fire test -	Class I	Pass
Critical Radiant Flux -	9.5 kW/m <sup>2</sup>	
Anti-static -	≤3.5 kV	Pass
Wear tests -	r =2.8	Pass
Warranties -	10 Year Wear Resistance Limited Warranty 10 Year Delamination Limited Warranty 10 Year Dimensional Stability Limited Warranty 10 Year Castor Chairs Limited Warranty 10 Year Stain Limited Warranty Life-time Static Limited Warranty	

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz

  
robert malcolm