Carpet Tile

Brenna

Specifications:















Solution dyed nylon

Antistatic

Long lasting

Dimensional stability

l Fade resistant

ade Castor who istant resistant

Construction -Multi-level Loop Fibre -100% Solution Dyed Nylon 1/12" Gauge -Stitches 11 per inch Pile weight -20 oz/yd² Average pile height -4 mm ± 0.5 mm **PVC** with Fiberglass Backing -Tile size -50 cm x 50 cm Traffic classification -Commercial - Heavy Duty Antimicrobial -Ultra-Fresh Quarter Turn; Monolithic; Brick; Ashlar Installation method -Class I Fire test -**Pass** Critical Radiant Flux -5.2 kW/m2 ≤3.5 kV Anti-static -Wear tests r = 2.8**Pass** Warranties -10 Year Wear Resistance Limited Warranty 10 Year Delamination Limited Warranty 10 Year Dimensional Stability Limited Warranty 10 Year Castor Chairs Limited Warranty 10 Year Stain Limited Warranty Life-time Static Limited Warranty

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under castor wheels to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand robertmalcolm.co.nz

