

# Commercial Vinyl Centra 2021

## Specifications:



Domestic  
heavy




Commercial  
very heavy



Industrial  
heavy



Slip  
resistant




Dimensional  
stability



Thermal  
resistance



Chemical  
resistant



Light  
fastness

	<u>Centra 1</u>	<u>Centra 2</u>
Level of use -	33 – 42	23 – 34 - 43
Total thickness -	2.30 mm	2.00 mm
Wear layer -	0.60 mm	0.70 mm
Wear layer PUR treatment -	HyperGuard+	HyperGuard+
Total weight -	2200 g/m <sup>2</sup>	2543 g/m <sup>2</sup>
Width -	2 m	2 m
Standard length -	30 m	25 m
Inflammability -	Bfl-S1	Bfl-S1
Slip resistance -	DS	DS
Slip restraint -	R10	R10
Residual indentation -	0.20 mm	0.05 mm
Furniture leg resistance -	Very good	Very good
Electrical resistance -	10 <sup>9</sup> Ohm	10 <sup>9</sup> Ohm
Dimensional stability -	0.10 %	0.05 %
Heat insulation -	0.0108 (m <sup>2</sup> .K/W)	0.0080 (m <sup>2</sup> .K/W)
Light fastness -	6-7	6
Underfloor heating -	Suitable	Suitable
Resistance to chemicals -	Very good	Very good
Warranty	5 years	5 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm

