

# Carpet Tile

# City Lights


## Specifications:



Solution dyed nylon



Antistatic covering



Fade resistant



Castor wheel resistant



Construction -	Multi-level loop
Fibre -	100% Solution Dyed Nylon
Gauge -	1/12"
Stitches -	10 per inch
Pile weight -	18 oz/yd <sup>2</sup>
Average pile height -	4 mm ± 0.5 mm
Backing -	PVC with fiberglass
Tile size -	50 cm x 50 cm
Traffic classification -	Heavy Duty Commercial
Antimicrobial -	Health Guard
Installation method -	Quarter Turn; Monolithic; Brick; Ashlar
Fire test -	Class I Pass
Critical Radiant Flux -	9.5 kW/m <sup>2</sup>
Anti-static -	≤3.5 kV Pass
Wear tests -	r =2.8 Pass
Warranties -	10 Year Wear Resistance Limited Warranty 10 Year Delamination Limited Warranty 10 Year Dimensional Stability Limited Warranty 10 Year Castor Chairs Limited Warranty 10 Year Stain Limited Warranty Life-time Static Limited Warranty

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm

