


Commercial Carpet

Coastline

Specifications:




Solution dyed



Antistatic covering



Stain resistant



Light fastness



5 year guarantee

Pile fibre -	100% Solution Dyed Polypropylene
Colouration -	75% Solution Dyed / 25% Twisted
Machine gauge -	1/10 th Gauge
Construction -	Level Loop Graphic
Width -	3.66 m (12')
Stitch rate -	34 per 100 mm
Tufted pile weight -	20 oz/yd ² 678 g/m ² (± 5%)
Tufted pile height -	4.5 mm (± 5%)
Primary backing -	Woven Synthetic
Secondary backing -	Easybac®
9A Fire rating -	No
9B Fire rating	Yes (Building is fitted with sprinkler system complying with specification E1.5)
Static generation (AS2834) -	< 3.5 kV
Light fastness -	6 – 7
Resistance to change on wet cleaning -	4 – 5
Pattern repeat -	35 mm x 35 mm
Grading -	Residential Medium Duty + Stairs Commercial Medium Duty
Warranties -	5 Year Limited Anti-Static 5 Year Limited Manufacturing / Wear 5 Year Limited Stain Resistance

- Due to dye lot variations, actual material may vary from sample.
- Chair mats are mandatory.
- This carpet must be laid in accordance with AS/NZ Installation Standards.
- All joins must be seam sealed.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

