Commercial Carpet

Directors Office

Specifications:













Solution dyed nylon

Pile fibre -

Width -

Stitch rate -

Colouration -

Machine gauge - Construction -

Tufted pile weight -Tufted pile height -

Primary backing -

9A Fire rating -

9B Fire rating

Light fastness -

Pattern repeat -

Secondary backing -

Static generation (AS2834) -

Resistance to change on wet cleaning -

Antistatio

Stain resistant

Light fastness

100% Resistain® Solution Dyed Nylon
Solution Dyed
1/10th Gauge
Modulated Loop
3.66 m (12')
58 / 100 mm
26 oz/yd² |881 g/m² (± 5%)
3 - 5 mm (± 5%)
Woven Synthetic
Easybac®
Yes

Grading -	Residential Extra Heavy Duty + Stairs 6*
	Commercial Extra Heavy Duty + Stairs 4*
Warranties -	15 Year Limited Anti-Static
	15 Year Limited Soil Resistance
	15 Year Limited Stain Resistance

Yes

6 - 7 4 - 5

< 3.5 kV

10 mm x 10 mm

- Due to dye lot variations, actual material may vary from sample.
- Chair mats are mandatory.
- This carpet must be laid in accordance with AS/NZ Installation Standards.
- All joins must be seam sealed.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 **e** office@robertmalcolm.co.nz 59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand **robertmalcolm.co.nz**

