



NATURAL
TEXTURE
EMBOSSED IN REGISTER

Divino

HOLLYFORD 52932



Size 19,6 x 132,0 cm
Thickness 2,5 mm
Wearlayer 0,55 mm

4 SIDED BEVELLED EDGES 



Benefits



Moisture resistant

An easy clean moisture resistant wear layer makes design flooring suitable for any room, even bathrooms and kitchens.



Soundproof

Design flooring absorbs sound, giving better acoustics in the home or working environment.



Hygienic

No expensive cleaning agents are required to keep your floor at its best; just a simple broom, mop and vacuum cleaner. A design floor will not harbor dust mites and other allergens.



IAQ – Indoor Air Quality

As far as air quality is concerned, all design floors adhere to the German AgBB standard, the strictest air quality standard in the world.



Superguard®

The upper Superguard® layer is scuff and stain resistant and is easy to clean, offering maximum protection with minimum maintenance.



No marks and spots

Thanks to their strong wear layer, combined with the PU layer, our design floors are specifically resistant to spots and shoe marks, which can be removed within a moment.



Minimal residual indentation

Our design floors adhere to all strict standards concerning residual indentations caused by chairs, cupboards, heels, etc.



Technical specifications dryback



PRODUCT INFORMATION		
Level of use	EN ISO 10874	23 - 33 - 42
Total thickness	EN ISO 24346	2,5 mm (100 mils)
Wear layer	EN ISO 24340	0,55 mm (22 mils)
Wear layer PUR treatment		Superguard®
Total weight g/m²	EN ISO 23997	4.059
		Embossed in register

SIZE & PACKING		
Planks	EN ISO 24342	19,6 x 132,0 cm
Box planks	14 pcs/box	3,62 m²/box

TEST RESULTS		
Inflammability	EN 13501	Bfl-S1
Slip resistance	EN 13893	DS
Slip restraint	DIN 51130	R10
Warranty (year)		20 Residential 10 Commercial

The warranty covers manufacturing defects and premature wear in the event of normal use.

The samples in this presentation are only cuttings of the respective products and show only a small part of the overall design and colour. With regard to colour printing of the photographic images, it is only possible to give a provisional representation of the colour.

Installation

Dryback flooring has to be **glued** completely onto a solid and smooth **subfloor**.

A suitable PVC adhesive therefore has to be used.

RML's Divino Collection must be installed in accordance with the NZ Building Code Standard NZS AS 1884-2013 using an RML Floors Recommended Adhesive.

