



ORARI 80883



HOLLYFORD 52932



MOTU 53830



RANGITIKI 53967

RML - 19/2018 - (MBC) 6402

Divino collection

## Benefits



### Moisture resistant

An easy clean moisture resistant wear layer makes design flooring suitable for any room, even bedrooms and kitchens.



### Soundproof

Design flooring absorbs sound, giving better acoustics in the home or working environment.



### Hygienic

No expensive cleaning agents are required to keep your floor in its best, just a simple broom, mop and vacuum cleaner. A design floor will not harbour dust mites and other allergens.



### IAQ – Indoor Air Quality

As far as air quality is concerned, all design floors adhere to the German DIN standard, the strictest air quality standard in the world.



### Superguard®

The SuperGuard® layer is scuff and stain resistant and is easy to clean, offering maximum protection with minimum maintenance.



### No marks and spots

Thanks to their strong wear layer, combined with the PU layer, our design floors are specifically resistant to spots and shoe marks, which can be removed within a moment.



### Minimal residual indentation

Our design floors adhere to all strict standards concerning residual indentation's caused by chairs, cupboards, trolleys, etc.



## Technical specifications dryback



PRODUCT INFORMATION			
Level of use	EN ISO 10874	23 - 33 - 42	
Total thickness	EN ISO 24346	2.5 mm	
Wear layer	EN ISO 24340	0.55 mm	
Wear layer PUR treatment		Superguard®	
Total weight	EN ISO 23897	4.059 g/m <sup>2</sup>	
		Embossed in register	
SIZE & PACKING			
Planks	EN ISO 24342	19,6 x 132,0 cm	
Box planks		14 pcs/box	3,62 m <sup>2</sup> /box
TEST RESULTS			
Inflammability	EN 13501	BI-s1	
Slip resistance	EN 13893	D5	
Slip resistance	DIN 51130	R10	
Warranty (year)		20 Residential   10 Commercial	

The warranty covers manufacturing defects and premature wear in the event of normal use.

The samples in this presentation are only cuttings of the respective products and show only a small part of the overall design and colour. With regard to colour printing of the photographic images, it is only possible to give a provisional representation of the colour.

## Installation

Dryback flooring has to be **glued** completely onto a solid and smooth **subfloor**. A suitable PVC adhesive therefore has to be used.



RML's Divino Collection must be installed in accordance with the NZ Building Code Standard NZS AS 1984-2013 using an RML Floors Recommended Adhesive.



robert malcolM

Tel 033669839  
www.robertmalcolM.co.nz



robert malcolM

Divino collection



# Divino

100%  
DESIGNED AND  
PRODUCED IN  
EUROPE

MOTU 53830



KAITUNA 53117




HAWDON 81937



KAITUNA 53117



BULLER 52945

 robert malcolm

Size **19,6 x 132,0 cm**  
Thickness **2,5 mm**  
Wearlayer **0,55 mm**

4 SIDED BEVELLED EDGES



Divino collection



RANGITIKI 53967



MOTU 53830



MOHAKA 53930



KAITUNA 53117



DART 53926



LOCKY 53850



STONY 53870



CLARENCE 80827



ORARI 80883



PEARSON 80995



HOLLYFORD 52932



GI ENROY 52232



BULLER 52945



WAIHOPAI 81249



CLUTHA 81872



HAWDON 81937