

Porcelain Everquartz

Specifications:



Environmentally
Friendly



Slip
resistant



Chemical
resistant




Stain
resistant



Abrasion
resistance



Thermal
resistance



Long
lasting



10
year guarantee

Dimension -	600 x 600 mm	
Water absorption -	• 0.07%, Super Polished	• 0.03%, Honed
Determination of dimensions -	<ul style="list-style-type: none"> • Sides max 0.4% • Warpage max 0.1% • Straightness of sides 0.0% • Edge curvature max 0.1% 	<ul style="list-style-type: none"> • Thickness max 1.1% • Rectangularity max 0.2% • Centre curvature 0.0% • Surface defects 0.0%
Breaking strength -	• 2040N / 452 lbf, all surfaces	
Abrasion strength -	114.3mm ³ , all surfaces	
Thermal shock resistance -	No damage, all surfaces	
Slip resistance I (Oil wet ramp test) -	• 6.4° - R9, Super Polished	• 5.3° - Class N/A, Honed
Slip resistance II (Wet pendulum test) -	Wet: 23 - Z - P1, all surfaces	
Slip resistance III (Dynamic coefficient of friction) -	• Wet: 0.29, Super Polished	• Wet: 0.44, Honed
Chemical resistance -	Passed, all surfaces (Household and Pool Chemicals)	
Stain resistance -	Passed, all surfaces	
Frost resistance -	No damage, all surfaces	
Shade variation -	Within V1, all surfaces	
Warranty (year) -	10 Years	

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

