Residential Vinyl Fashion

Specifications:

	32 ommercial general	Slip resistant	Reduces	Light fastness	Thermal resistance	Chemical resistant	15	
European classification -			23 - 32	2				
Total thickness -			2.40 m	2.40 mm				
Wear layer -			0.35 m	0.35 mm				
Wear layer treatment -			MAT E	MAT Effect				
Total weight -			1730 g	1730 g/m ²				
Width -			2 m	2 m				
Standard Length			25 m	25 m				
Slip resistance -			R10	R10				
Inflammability -			Cfl-S1	Cfl-S1				
Acoustical insulation -			16 dB	16 dB				
Light fastness -			≥ 6					
Underfloor heating -			Suitabl	Suitable				
Thermal resistance -			0.06 m	0.06 m²/kW				
Resistance to household chemicals -			ОК	ОК				
Warranty (year) -			15 yea	15 years (Residential use)				

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839
e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



