


L.V.T.

Floorworks Classic Plus

Specifications:



Dimensional stability



Slip resistant



Long lasting




Thermal resistance



Great for families



Hypoallergenic



Stocked in New Zealand

Total thickness -	2.00 mm
Wear layer -	0.30 mm
Wear layer PUR treatment -	Hexamoll DINCH
Total weight g/M ² -	3031.3 g/m ²
Planks -	121.9 x 18.4 cm
Box planks -	3.34 m ² /box
Inflammability -	Bfl-S1
Squareness & straightness -	Side length mean value – 457.3mm Squareness mean value – 0.038mm Straightness mean value – 0.043mm
Slip resistance -	R10
Residual indentation -	0.03 mm after 150 minutes
Furniture leg resistance -	Applied mass 32kg, no visible damage
Dimensional stability -	≤ 0.25 %,
Castor chair resistance -	No visible damage
Underfloor heating -	Suitable, max 27°C
Warranty -	12 years residential

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

