


L.V.T.

Floorworks Classic Plus

Specifications:



Dimensional stability




Slip resistant




Long lasting




Thermal resistance



Great for families



Hypoallergenic



Stocked in New Zealand

Total thickness -	2.00 mm
Wear layer -	0.30 mm
Wear layer PUR treatment -	Hexamoll DINCH
Total weight g/M ² -	3031.3 g/m ²
Planks -	121.9 x 18.4 cm
Box planks -	3.34 m ² /box
Inflammability -	Bfl-S1
Squareness & straightness -	Side length mean value – 457.3mm Squareness mean value – 0.038mm Straightness mean value – 0.043mm
Slip resistance -	R10
Residual indentation -	0.03 mm after 150 minutes
Furniture leg resistance -	Applied mass 32kg, no visible damage
Dimensional stability -	≤ 0.25 %
Castor chair resistance -	No visible damage
Underfloor heating -	Suitable, max 27°C
Warranty -	12 years residential

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

