

# Commercial Vinyl Forum

## Specifications:




Commercial  
very heavy




Industrial  
heavy



Slip  
resistant



Dimensional  
stability



Light  
fastness



Thermal  
resistance



Chemical  
resistant



10  
year guarantee

Level of use -	34 – 43
Total thickness -	2.00 mm
Wear layer -	0.40 mm
Wear layer PUR treatment -	TopClean
Total weight -	2150 g/m <sup>2</sup>
Width -	2 m
Standard length -	25 m
Inflammability -	5.9 KW/m <sup>2</sup>
Slip resistance -	R10
Residual indentation -	≤ 0.10 mm
Electrical resistance -	< 2 kV on concrete / R1 > 10 Ω
Dimensional stability -	≤ 0.40 %
Light fastness -	≥ Level 6
Underfloor heating -	Suitable
Resistance to chemicals -	High resistance
Warranty (year) -	10 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm

