

Residential Vinyl

Belgo 2017

Specifications:




Domestic
heavy



Commercial
moderate




Slip
resistant




Reduces
noise



Thermal
resistance



Great for
families



Stocked in
New Zealand



Protectonite
PU

| | |
|-------------------------------------|---------------------------|
| European classification - | 23 – 32 |
| Total thickness - | 2.60 mm |
| Wear layer - | 0.35 mm |
| Wear layer treatment - | PU / Natural Feel |
| Total weight - | 1800 g/m ² |
| Width - | 3 m |
| Standard length - | 25 m or 30 m |
| Slip resistance - | R10 |
| Inflammability - | Cfl-S1 |
| Acoustical insulation - | 18 dB |
| Underfloor heating - | Suitable |
| Thermal conductivity - | 0.25 W / mK |
| Thermal resistance - | 0.0104 m ² K/W |
| Resistance to household chemicals - | Very good |
| Warranty - | 15 years |

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

