









Commercial Vinyl Centra

Specifications:

								
	Domestic heavy	Commercial very heavy	Industrial heavy	Slip resistant	Dimensional stability	Thermal resistance	Chemical resistant	Light fastness
Level of use -	23 – 34 – 43							
Total thickness -	2.00 mm							
Wear layer -	0.70 mm							
Wear layer PUR treatment -	Hyperguard+®							
Total weight -	2963 g/m ²							
Width -	2 m							
Standard length -	25 m							
Inflammability -	Bfl-S1							
Slip resistance -	DS							
Slip restraint -	R10							
Residual indentation -	0.05 mm							
Furniture leg resistance -	Very good							
Electrical resistance -	10 ⁹ Ohm							
Dimensional stability -	0.05 %							
Heat insulation -	0.25 w/(m.K)							
Light fastness -	6							
Underfloor heating -	Suitable							
Resistance to chemicals -	Very good							
Warranty (year) -	5 years Commercial							

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

