Residential Vinyl

Picasso

Specifications:

















Domestic medium

Natural

Slip resistant

Reduces

Thermal

Protectonite

Great for

Stocked in New Zealand

European classification -	22
Total thickness -	3.00 mm
Wear layer -	0.20 mm
Wear layer treatment -	PU / Natural Feel
Total weight -	1850 g/m²
Width -	2 m
Standard length -	30 m
Slip resistance -	R9 – R11
Inflammability -	Cfl-S1
Acoustical insulation -	18 dB
Underfloor heating -	Suitable
Thermal conductivity -	0.25 W / mK
Thermal resistance -	0.0120 m ² K/W
Resistance to household chemicals -	Very good
Warranty (year) -	5 years

• RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 **e** office@robertmalcolm.co.nz 59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand **robertmalcolm.co.nz**

