

Residential Vinyl Step

Specifications:



Domestic heavy



Natural feel



Slip resistant




Reduces noise




Thermal resistance



Protectonite PU



Long lasting



Stocked in New Zealand

European classification EN ISO 10874 -	23- 32
Total thickness -	2.40 mm
Wear layer -	0.25 mm
Wear layer treatment -	PU
Total weight -	1850 g/m ²
Width -	2 m & 3 m
Standard length -	30 m
Slip resistance DIN 51130 -	R10
Inflammability EN 13501 -	Cfl-S1
Acoustical insulation ISO 717 -	18 dB
Underfloor heating -	Suitable
Thermal conductivity EN 12524 -	0.25 W / mK
Thermal resistance EN ISO 12466-	0.0088 m ² K/W
Resistance to household chemicals -	Very good
Warranty (year) -	10 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, Christchurch 8042, New Zealand
robertmalcolm.co.nz



robert malcolm

