

Residential Vinyl Step

Specifications:




Domestic
medium



Natural
feel



Slip
resistant




Reduces
noise




Thermal
resistance



Protectonite
PU



Long
lasting



Stocked in
New Zealand

European classification -	22
Total thickness -	2.80 mm
Wear layer -	0.20 mm
Wear layer treatment -	Natural Feel
Total weight -	1600 g/m ²
Width -	2 m
Standard length -	30 m
Slip resistance -	R10
Inflammability -	Cfl-S1
Acoustical insulation -	18 dB
Underfloor heating -	Suitable
Thermal conductivity -	0.25 W / mK
Thermal resistance -	0.0112 m ² K/W
Resistance to household chemicals -	Very good
Warranty (year) -	5 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz


robert malcolm

