

# Residential Vinyl Tundra

## Specifications:



Domestic  
heavy



Commercial  
moderate




Natural  
feel




Slip  
resistant




Thermal  
resistance



Reduces  
noise



Long  
lasting



Stocked in  
New Zealand

European classification -	23 – 31
Total thickness -	3.00 mm
Wear layer -	0.30 mm
Wear layer treatment -	PU / Natural Feel
Total weight -	2250 g/m <sup>2</sup>
Width -	3 m
Standard length -	30 m
Slip resistance -	R11
Inflammability -	Bfl-S1
Acoustical insulation -	15 dB
Underfloor heating -	Suitable
Thermal conductivity -	0.25 W / mK
Thermal resistance -	0.0120 m <sup>2</sup> K/W
Resistance to household chemicals -	Very good
Warranty (year) -	15 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e [office@robertmalcolm.co.nz](mailto:office@robertmalcolm.co.nz)  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
[robertmalcolm.co.nz](http://robertmalcolm.co.nz)

  
robert malcolm

