


Carpet Tile Millbrook – Bedford


Specifications:




Solution dyed



Antistatic covering



Dimensional stability



Fade resistant



Stain resistant



5 year guarantee

Construction -	Multi Level Loop Pile
Fibre -	Solution Dyed PP
Gauge -	1/12"
Pile weight -	21 oz/yd ²
Average pile height -	3.5 mm, ± 5%
Backing -	PVC with Fibreglass
Tile size -	50 cm x 50 cm
Installation method -	Quarter Turn Only
Anti-static -	AATCC 134 < 3.5kV
Warranties -	5 Year Limited Wear 5 Year Limited Backing Integrity 5 Year Limited Edge Ravel 5 Year Limited Dimensional Stability 5 Year Limited Static Protection

- Warranties are extended to the original purchaser of the product only and are not transferable.
- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

