


L.V.T.

Moduleo Moods

Specifications:




Dimensional stability




Castor wheel resistant




Thermal resistance



Antistatic covering




Stain resistant



Long lasting



Great for families



Bacteria and mould resistant

Level of use -	23 – 33 – 42		
Total thickness -	2.5 mm		
Wear layer -	0.55 mm		
Wear layer PUR treatment -	Protectonite®		
Total weight -	4059 g/m ²		
Size & Packaging -	Size (mm)	Pieces/box	M ² /box
Slim Plank	522.67 x 65.33	58	1.98
Chevron	522.67 x 92.40	42	2.03
Hexagon	226.32 x 196.00	44	1.46
Diamond	(Indent Product) 113.16 x 196.00	132	1.46
Triangle	(Indent Product) 452.64 x 392.00	17	1.51
Short Plank	(Indent Product) 522.67 x 130.67	29	1.98
Small Plank	(Indent Product) 261.33 x 65.33	116	1.98
Medium Plank	(Indent Product) 784.00 x 196.00	13	2.00
Inflammability -	Bfl-S1		
Scratch resistance -	Class T		
Squareness & straightness -	≤ 0.25 mm		
Slip resistance -	DS		
Slip restraint -	R10		
Residual indentation -	Norm: ≤ 0.10 mm, Average result measured ≤ 0.03 mm		
Furniture leg resistance -	No cracks, no damage		
Electrical resistance -	≤ 10 ⁹ Ohm		
Dimensional stability -	Norm: ≤ 0.25 %, Average result measured ≤ 0.05 %		
Heat insulation -	0.25 w/(m.K)		
Thermal resistance R -	0.0100 m ² K/W		
Electrostatic performance -	< 2 kV		
Acoustic insulation -	4 dB		
Castor chair resistance -	No damage to wearlayer, no delamination		
Stain resistance -	Very good		
Light fastness -	≥ 6		
Underfloor heating -	Suitable, max 27°C		
Warranty (year) -	20 Residential / 10 Commercial		

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm