


L.V.T.

Moduleo Moods

Specifications:




Dimensional stability




Castor wheel resistant



Thermal resistance



Antistatic covering




Stain resistant



Long lasting



Great for families



Bacteria and mould resistant

Level of use -	23 – 33 – 42		
Total thickness -	2.5 mm		
Wear layer -	0.55 mm		
Wear layer PUR treatment -	Protectonite®		
Total weight -	4059 g/m ²		
Size & Packaging -	Size (mm)	Pieces/box	M ² /box
Slim Plank	522.67 x 65.33	58	1.98
Chevron	522.67 x 92.40	42	2.03
Hexagon	226.32 x 196.00	44	1.46
Diamond (Indent Product)	113.16 x 196.00	132	1.46
Triangle (Indent Product)	452.64 x 392.00	17	1.51
Short Plank (Indent Product)	522.67 x 130.67	29	1.98
Small Plank (Indent Product)	261.33 x 65.33	116	1.98
Medium Plank (Indent Product)	784.00 x 196.00	13	2.00
Inflammability -	Bfl-S1		
Critical Radiant Flux -	8.9kW/m ²		
Scratch resistance -	Class T		
Squareness & straightness -	≤ 0.25 mm		
Slip resistance -	DS		
Slip restraint -	R10		
Residual indentation -	Norm: ≤ 0.10 mm, Average result measured ≤ 0.03 mm		
Furniture leg resistance -	No cracks, no damage		
Electrical resistance -	≤ 10 ⁹ Ohm		
Dimensional stability -	Norm: ≤ 0.25 %, Average result measured ≤ 0.05 %		
Heat insulation -	0.25 w/(m.K)		
Thermal resistance R -	0.0100 m ² K/W		
Electrostatic performance -	< 2 kV		
Acoustic insulation -	4 dB		
Castor chair resistance -	No damage to wearlayer, no delamination		
Stain resistance -	Very good		
Light fastness -	≥ 6		
Underfloor heating -	Suitable, max 27°C		
Warranty (year) -	20 Residential / 10 Commercial		

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request sample or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

L.V.T.

Moduleo Moods

Specifications:

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm