


# Carpet Tile

# Montage


## Specifications:




Solution dyed nylon




Antistatic covering



Long lasting




Dimensional stability



Fade resistant



Castor wheel resistant



10 year guarantee

Construction -	Multi-level loop		
Fibre -	100% Econyl Nylon, 100% Recycled Content		
Dye Method	100% Solution Dyed Nylon		
Gauge -	1/10"		
Stitches -	12 per inch		
Pile weight -	20 oz/yd <sup>2</sup>		
Average pile height -	4 mm ± 0.5 mm		
Backing -	PVC with fiberglass		
Tile size -	50 cm x 50 cm		
Sound Absorption -	BS EN ISO 354 Absorption Coefficient – NRC = 0.15		
Traffic classification -	Class II, Heavy Commercial		
Antimicrobial -	Health Guard		
Installation method -	Quarter Turn		
Fire test -	Radiant Panel	Class I	Pass
	Methenamine Pill	8	Pass
	Smoke Density	≤ 450	Pass
Anti-static -	Static Propensity	≤3.5 kV	Pass
Wear tests -	Castor Chair	r = 2.8	Pass
Warranties -	10 Year Wear Resistance Limited Warranty		
	10 Year Delamination Limited Warranty		
	10 Year Dimensional Stability Limited Warranty		
	10 Year Castor Chairs Limited Warranty		
	10 Year Stain Limited Warranty		
	Life-time Static Limited Warranty		

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller castors to protect the appearance retention of the product and to avoid excessive wear in these areas.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz

