

Residential Vinyl Nomad

Specifications:




Domestic
heavy



Commercial
general



Slip
resistant




Reduces
noise



Thermal
resistance



Great for
families



Stocked in
New Zealand



Hyperguard +

European classification -	23 – 32
Total thickness -	3.90 mm
Wear layer -	0.45 mm
Wear layer treatment -	HyperGuard +
Total weight -	2850 g/m ²
Width -	3 m
Standard length -	20 m
Slip resistance -	R10
Inflammability -	Bfl-S1
Acoustical insulation -	LW 20 dB
Underfloor heating -	Suitable
Thermal conductivity -	0.25 W / mK
Heat insulation -	0,0156 (m ² .K/W)
Resistance to household chemicals -	Very good
Warranty -	15 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm