


Residential Vinyl Renaissance


Specifications:



Slip
resistant



Reduces
noise



Light
fastness



Thermal
resistance



Chemical
resistant

European classification -	23 / 41	22
Total thickness -	2.40 mm	2.60 mm
Wear layer -	0.35 mm	0.22 mm
Surface treatment -	Extreme Protection	
Total weight -	1580 g/m ²	1580 g/m ²
Width -	2 m & 3 m	2 m & 3 m
Standard length -	25 m	30 m
Slip resistance -	R10	
Inflammability -	Cfl-S1	Bfl-S1
Acoustical insulation -	16 dB	
Light fastness -	≥ 6	
Underfloor heating -	Suitable (maximum 27C)	
Thermal resistance -	0.03 m ² /kW	0.04 m ² /kW
Chemical resistance -	OK	
Warranty (year) -	15 years (Residential use)	10 years (Residential use)

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm