

Porcelain & Mosaics

Sandstone

Specifications:



Environmentally
Friendly



Slip
resistant



Chemical
resistant



Stain
resistant



Abrasion
resistance



Thermal
resistance



10
year guarantee

Dimension -	600 mm x 600 mm, 600 mm x 300 mm	
Water absorption -	0.10%	
Determination of dimensions -	<ul style="list-style-type: none"> • Length max 0.14% • Warpage max 0.5% • Straightness of sides max 0.21% • Centre curvature max 0.05% 	<ul style="list-style-type: none"> • Thickness max 2.1%, • Rectangularity max 0.23% • Edge curvature max 0.07%
Breaking strength -	2586N	
Abrasion strength -	Class 4	
Thermal shock resistance -	No damage	
Slip resistance I (Oil wet ramp test) -	22.5° - R11	
Slip resistance II (Wet pendulum test) -	Class X	
Slip resistance III (Dynamic coefficient of friction) -	0.64	
Chemical resistance -	Passed (UA)	
Stain resistance -	Passed	
Frost resistance -	No damage	
Warranty (year) -	10 Years	

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

