## Residential Vinyl Select

## **Specifications:**

| Domestic<br>heavy Comme<br>gene     | ercial Slip | Reduces | Light fastness             | Thermal<br>resistance | Chemical<br>resistant | 15 |  |
|-------------------------------------|-------------|---------|----------------------------|-----------------------|-----------------------|----|--|
| European classification -           |             |         | 2                          |                       |                       |    |  |
| Total thickness -                   |             |         | ım                         |                       |                       |    |  |
| Wear layer -                        |             |         | ım                         |                       |                       |    |  |
| Wear layer treatment -              |             |         | ffect                      |                       |                       |    |  |
| Total weight -                      |             |         | g/m²                       |                       |                       |    |  |
| Width -                             |             | 3 m     | 3 m                        |                       |                       |    |  |
| Standard Length                     |             | 25 m    | 25 m                       |                       |                       |    |  |
| Slip resistance -                   |             | R10     | R10                        |                       |                       |    |  |
| Inflammability -                    |             | Cfl-S1  | Cfl-S1                     |                       |                       |    |  |
| Acoustical insulation -             |             | 16 dB   | 16 dB                      |                       |                       |    |  |
| Light fastness -                    |             |         |                            |                       |                       |    |  |
| Underfloor heating -                |             |         | le                         |                       |                       |    |  |
| Thermal resistance -                |             |         | 0.06 m <sup>2</sup> /kW    |                       |                       |    |  |
| Resistance to household chemicals - |             |         | ОК                         |                       |                       |    |  |
| Warranty (year) -                   |             |         | 15 years (Residential use) |                       |                       |    |  |

• RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839
e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



