

Carpet Tile

Sumi Elite


Specifications:




Solution dyed nylon



Antistatic covering




Dimensional stability



Fade resistant



Stain resistant



Long lasting



Construction -	Tufted, High & Low Loop
Fibre -	Solution Dyed Nylon
Gauge -	1/8"
Stitches -	33/10 cm
Pile weight -	660 g/m ²
Total weight -	4.5kg/m ²
Average pile height -	4.5~3 mm (± 0.5 mm)
Backing -	ECOS – Post consumer recycled PVC
Tile size -	50 cm x 50 cm
Installation method -	Monolithic; Chequer Board
Fire test -	E2110115 (JIS L-1091:1999.8.2 – B)
Anti-static -	Less than 1000V (JIS L-4406, 23°C, 25% RH, synthetic sole)
Warranties -	10 Year Limited Wear 10 Year Limited Edge Ravel 10 Year Limited Zippering 10 Year Limited Delamination

- All product specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product specifications may change without notice as long as product performance is not materially affected.
- Must be laid in accordance with AS/NZ installation standards.
- We recommend the use of protective chair pads under office chairs with roller casters to protect the appearance retention of the product and to avoid excessive wear in these areas.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

