

Residential Vinyl Supreme

Specifications:




Domestic
heavy




Commercial
general



Slip
resistant



Reduces
noise



Light
fastness



Thermal
resistance



Chemical
resistant



15
year guarantee

European classification -	23 – 32
Total thickness -	3.70 mm
Wear layer -	0.35 mm
Wear layer treatment -	MAT Effect
Total weight -	2700 g/m ²
Width -	3 m
Standard length -	24 m
Slip resistance -	R10
Inflammability -	Cfl-S1
Acoustical insulation -	17 dB
Light fastness -	≥ 6
Underfloor heating -	Suitable
Thermal resistance -	0.06 m ² /kW
Resistance to household chemicals -	OK
Warranty (year) -	15 years (Residential use)

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

