


L.V.T. Supremo

Specifications:



Dimensional stability




Slip resistant




Castor wheel resistant



Thermal resistance




Long lasting



Antistatic covering



Great for families



Stocked in New Zealand

Level of use -	23 – 31
Total thickness -	2.00 mm
Wear layer -	0.30 mm
Wear layer PUR treatment -	Superguard
Total weight -	3800 g/m ²
Planks -	18.42 x 121.92 cm
Box planks -	17 pc/box, 3.82 m ² /box
Inflammability -	Bfl-S1
Scratch resistance -	Type I
Squareness & straightness -	≤ 0.35 mm
Slip resistance -	DS
Slip restraint -	R10
Residual indentation -	≤ 0.10 mm
Furniture leg resistance -	No cracks, no damage
Electrical resistance -	≤ 10 ⁹ Ohm
Dimensional stability -	≤ 0.25 %
Heat insulation -	0.25 w/(m.K)
Thermal resistance R -	0.0100 m ² K/W
Electrostatic performance -	< 2 kV
Acoustic insulation -	4 dB
Castor chair resistance -	No damage to wearlayer, no delamination but only when fixated
Stain resistance -	Good
Light fastness -	≥ 6
Underfloor heating -	Suitable, max 27°C
Warranty (year) -	12 Residential / 5 Commercial

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

