## **Commercial Carpet**

## **Tactics 20**

## **Specifications:**













Solution

Pile fibre -

Width -

Stitch rate -

Colouration -

Machine gauge -Construction -

Tufted pile weight -Tufted pile height -

Primary backing -

9A Fire rating -

9B Fire rating

Light fastness -

Pattern repeat -

Grading -

Warranties -

Secondary backing -

100% Solution Dyed Polypropylene 87.5% Tri-colour, Solution Dyed / 12.5% Twisted 1/10<sup>th</sup> Gauge Level Loop Graphic 3.66 m (12') 52 / 100 mm 20 oz/yd2 | 949 g/m2 (± 5%) 5 mm (± 5%) Woven Synthetic Easybac® Yes (Building is fitted with sprinkler system complying with specification E1.5) Yes Static generation (AS2834) -< 3.5 kV 6 – 7 4 – 5 Resistance to change on wet cleaning -20 mm x 15 mm

Residential Extra Heavy Duty + Stairs Commercial Heavy Duty + Stairs

5 Year Limited Manufacturing / Wear 5 Year Limited Stain Resistance

5 Year Limited Anti-Static

5 Year Colourfast

- Due to dye lot variations, actual material may vary from sample.
- Chair mats are mandatory.
- This carpet must be laid in accordance with AS/NZ Installation Standards.
- All joins must be seam sealed.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

**p** 03 366 9839 **e** office@robertmalcolm.co.nz 59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand robertmalcolm.co.nz

