


Commercial Carpet

Tactics 20

Specifications:




Solution dyed




Antistatic covering



Stain resistant



Fade resistant



Light fastness



5 year guarantee

| | |
|--|---|
| Pile fibre - | 100% Solution Dyed Polypropylene |
| Colouration - | 87.5% Tri-colour, Solution Dyed / 12.5% Twisted |
| Machine gauge - | 1/10 th Gauge |
| Construction - | Level Loop Graphic |
| Width - | 3.66 m (12') |
| Stitch rate - | 52 / 100 mm |
| Tufted pile weight - | 20 oz/yd ² 949 g/m ² (± 5%) |
| Tufted pile height - | 5 mm (± 5%) |
| Primary backing - | Woven Synthetic |
| Secondary backing - | Easybac® |
| 9A Fire rating - | Yes (Building is fitted with sprinkler system complying with specification E1.5) |
| 9B Fire rating | Yes |
| Static generation (AS2834) - | < 3.5 kV |
| Light fastness - | 6 – 7 |
| Resistance to change on wet cleaning - | 4 – 5 |
| Pattern repeat - | 20 mm x 15 mm |
| Grading - | Residential Extra Heavy Duty + Stairs Commercial Heavy Duty + Stairs |
| Warranties - | 5 Year Limited Anti-Static 5 Year Colourfast 5 Year Limited Manufacturing / Wear 5 Year Limited Stain Resistance |

- Warranties are extended to the original purchaser of the carpet only and are not transferable.
- Due to dye lot variations, actual material may vary from sample.
- Chair mats are mandatory.
- This carpet must be laid in accordance with AS/NZ Installation Standards.
- All joins must be seam sealed.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

