

Commercial Vinyl Tarasafe Standard

Specifications:




Commercial
very heavy




Industrial
heavy



Slip
resistant



Dimensional
stability



Light
fastness



Thermal
resistance



Chemical
resistant

Level of use -	34 – 43
Total thickness -	2.00 mm
Wear layer -	0.85 mm
Total weight / m ² -	2460 gm/m ²
Width -	2 m
Standard length -	20 m
Inflammability -	Bfl-S1
Slip resistance -	R10
Residual indentation -	≤ 0.05
Dimensional stability -	≤ 0.40
Light fastness -	≥ 6
Underfloor heating -	Suitable
Resistance to chemicals -	Good
Warranty (year) -	12 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz



robert malcolm

