

# Commercial Vinyl Xtreme

## Specifications:



Commercial  
very heavy




Industrial  
heavy




Slip  
resistant




Thermal  
resistance



Dimensional  
stability



Light  
fastness



Stocked in  
New Zealand



Level of use -	34 – 43
Total thickness -	2.00 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	PU Laquer
Total weight -	2800 g/m <sup>2</sup>
Width -	2 m
Standard length -	22 m
Inflammability -	Bfl-S1
Critical Radiant Flux -	9.2kW/m <sup>2</sup>
Slip resistance -	DS
Slip restraint -	R10
Residual indentation -	≤ 0.10 mm
Dimensional stability -	≤ 0.40 %
Light fastness -	≥ 6
Underfloor heating -	Suitable
Warranty -	15 years

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm

